

TECHNICAL DATA SHEET
BASIC FLUORESCENT PAINT



1. Description

PintyPlus BASIC Fluorescent Paint is a quick dry acrylic enamel meant for the decoration both outdoors and indoors elements on a large range of materials.

2. Properties:

- Great resistance outdoors
- High adherence on any kind of materials
- Quick dry
- High visibility
- Very easy application and repainting
- It does not contain heavy metals

3. Recommended uses:

Suitable for use both indoors and outdoors. Recommended for decoration purposes, bricolage, labeling, stages, industry... The colours are much more luminous than the normal ones. The paint, when exposed to ultraviolet light, will feature very high fluorescent effects among a large variety. It may be used to create special effects using Black Light, too.

4. Presentation

Colours: Check colours shade card.

Cans: 520cc/400 ml and 270cc/200ml cans.

5. Technical Characteristics:

- | | |
|----------------------|--|
| • Nature | Modified acrylic resins |
| • Pigments | Fluorescent |
| • Solvents | Ketones , and in a great part, acetates |
| • Propellant | Hydrocarbons, rich in C3 y C4 |
| • Density | 0.95 ± 0.01 gr./cc (Depending on the colour) |
| • Viscosity | 13 – 14 seg. (Ford Cup Nr. 4, 20°C) |
| • % solids in weight | 36 ± 1 % (Theoretical value) |
| • VOC | 549 gr./l (Depending on the colour) |
| • Gloss at 60° | < 5% |

- Spreading: 520/400ml: 1-1,2 m² according to support
270/200ml: 0,5-0,6 m² according to support
- Drying time at 20°C: Superficial: 10 minutes
Total: 20 minutes
Repainted : After 15 minutes
- Application temperature from 5 up to 35°C
- Paint resistance to the heat Recommended up to 150°C
- Flammability Extremely flammable
- Pressure: 3-4 bars at 20°C
7-8 bars at 50°C
- Cleaning Cleaning solvent in spray
- Life of the product > 3 years

6. Instructions

The surface to be painted should be clean, dry and without any kind of pollutant. Shake the can well during 1 minute after hearing the ball rattles. Spray at a distance for 25/30 minutes applying thin, quick and criss-cross layers. Leave the layers to dry a few minutes. At the end of the application, turn the can over and spray until only gas comes out.

7. Security

The aerosol can features the correspondent security indications which must be followed. For further information please check the Security Data Sheet.

The information provided in the present technical sheet is the result of the research undertaken in our laboratory as well as real experiences based on applications. Nevertheless due to the fact that quite often the products are used in conditions beyond our control, we cannot warranty the good results of the product if the application and use are not the correct ones.



NOVASOL SPRAY S.A.

Polígono Industrial Empalme
C/ Empalme, 27
Tel. 977 67 76 05 Fax. 977 67 80 72
43712 LLORENÇ DEL PENEDÈS (Tarragona)
novasol@novasolspray.com