

TECHNICAL DATA SHEET

AQUA MATT COLORS



1. Description

Acrylic matt water-based paint for the protection and decoration of different surfaces either indoors or outdoors.

2. Properties:

- Great adherence
- Matt and smooth finish
- Excellent resistance to the atmospheric elements
- Low odour
- Very easy application
- Quick dry

3. Recommended uses:

Suitable for use both indoors and outdoors. Recommended to protect any kind of surface including expanded polystyrene: wood, metal, cardboard, stone, ceramics and many kinds of plastics. Ideal for crafts, fine arts, scrapbooking. Very suitable to paint at home, in reduced spaces.

4. Presentation

Colours: Check our Colours shade card

Cans: 210cc/150ml

5. Technical Characteristics:

- | | |
|----------------------|--|
| • Nature | Acrylic resin |
| • Solvents | Water and alcohol |
| • Propellant | DME |
| • Density | 1.02 ± 0.01 gr./cc |
| • Viscosity | 18 – 20 seg. (Copa Ford Nr. 4, 20°C) |
| • % solids in weight | 17,5 % (Theoretic value) |
| • VOC | 620 gr./l (Theoretic value) |
| • Gloss at 60° | <5 |
| • Spreading: | 210/150ml: 1 m ² according to support |

- Drying time at 20°C: Superficial: 1hour
Repainted : After 30 minutes
- Application temperature From 10 up to 35°C
- Paint resistance to the heat Recommended up to 90°C
- Flammability Extremely flammable
- Pressure: 5,5 bars at 20°C
7,5 bars at 50°C
- Cleaning During the first 15 minutes with water and soap, after this period of time, with alcohol
- Life of the product > 3 years

6. Instrucciones

The surface to be painted should be clean, dry and without any kind of pollutant.

Shake the can slightly. Spray at a distance for 25/30 minutes applying thin, quick and criss-cross layers. In order achieve a uniform finish and avoid any paint hang, it is advisable to apply two thin layers instead of a thick one. At the end of the application, turn the can over and spray until only gas comes out.

7. Security

The aerosol can features the correspondent security indications which must be followed. For further information please check the Security Data Sheet.

The information provided in the present technical sheet is the result of the research undertaken in our laboratory as well as real experiences based on applications. Nevertheless due to the fact that quite often the products are used in conditions beyond our control, we cannot warranty the good results of the product if the application and use are not the correct ones.



NOVASOL SPRAY S.A.

Polígono Industrial Empalme
Carretera de l'Arboç a Llorenç, Km. 4,7
Tel. 977 67 76 05 Fax. 977 67 80 72
43712 LLORENÇ DEL PENEDÈS (Tarragona)
novasol@novasolspray.com